Heavy Duty Silicone Rubber Drum and Pail Heaters

Product Highlights

/

Excellent solution for a wide range of poly and metal drum applications



Extra-wide 4" (102mm) heater coverage



Extra-long service life: Excellent durability and flexibility



Grounded heating element meets NEC 427.23



Easy adjustable thermostat control (°F or °C)







(see ordering options for details)

Specifications:

- Heating element is laminated between extra-thick layers of 20mil fiberglass reinforced silicone rubber
- Patented 360° grounded multi-stranded heating element is uniformily placed to maximize heat distribution
- Adjustable thermostat

50°F to 425°F (10-218°C) for metal[†] 50°F to 160°F (10-71°C) for plastic[†]

- Moisture and chemical resistant
- Choice of voltage: 120VAC or 240VAC
- 450°F (232°C) maximum exposure temperature on heating surface
- Dielectric strength of over 2000 volts
- Power cord 6-foot (1.8m) long

120V include standard 3-prong plug (NEMA 5-15) 240V has bare wire leads*

• Spring closure can be expanded 3" (76mm)

† If precise temperature control is required for your application, please contact BriskHeat or your local distributor for application assistance and product solutions.

Ordering Information:

- Heavy Duty (DHCS and DPCS series): Designed with two extra-thick layers of fiberglass reinforced silicone rubber for excellent strength and durability.
- Extra Heavy Duty (DHCH and DPCH series): Longest lasting and most durable drum heater. Designed with three extra-thick layers of fiberglass reinforced silicone rubber for ultimate strength and durability.

For Metal Drums/Pails

of Metal Brottis, Falls						
Size	Watts	Heavy Duty		Extra Heavy Duty		
Gallon (Liter)		120VAC	240VAC	120VAC	240VAC	
5 (19)	550	DHC\$10	DHCS20*	DHCH10	DHCH20*	
16 (61)	700	DHC\$11	DHCS21*	DHCH11	DHCH21*	
30 (114)	1000	DHCS13	DHCS23*	DHCH13	DHCH23*	
55 (208)	1200	DHC\$15	DHCS25*	DHCH15	DHCH25*	

Extra-Wide Extra-Strong Easier-to-Use

Standard Drum & Pail Heater Sizes

Sidildala Divili & Fall nealer Sizes						
Size Gallon (Liter)	Diameter in (mm)	Length in (mm)	Width in (mm)			
5 (19)	11.1 (282)	35.0 (889)	4 (102)			
15 (57) & 16 (61)	14.0 (355)	44.0 (1118)	4 (102)			
30 (114)	18.6 (473)	58.5 (1486)	4 (102)			
55 (208)	22.3 (566)	70.0 (1778)	4 (102)			

Accessories

Part Number	Description		
10180	Replacement spring for BriskHeat® Silicone Rubber Drum Heaters		

For Poly (Non-Metal) Drums/Pails

1	, <u>, , , , , , , , , , , , , , , , , , </u>						
	Size	Watts	Heavy Duty		Extra Heavy Duty		
	Gallon (Liter)		120VAC	240VAC	120VAC	240VAC	
	5 (19)	150	DPCS10	DPCS20*	DPCH10	DPCH20*	
	15 (57)	200	DPC\$11	DPCS21*	DPCH11	DPCH21*	
	30 (114)	250	DPCS13	DPCS23*	DPCH13	DPCH23*	
	55 (208)	300	DPCS15	DPCS25*	DPCH15	DPCH25*	

^{* 240}VAC Fahrenheit models have bare wire leads. 240VAC Celsius models have crimped wire ferrule terminated leads.

Ordering Options:

- A. Celsius Label Option: Add a "-C" at the end of the part number.
- B. CSA Approved Option: Add an "A" at the end of the part number. Includes bare wire leads.
- C. Drum Heater without controlling thermostat: Replace "C" with "N" in part number. External control is required with this option.