

TUBE LENGTH AIR HEATERS

and many more!



5/8

1/2

3/4

OPTIONS

- Male or Female pipe thread on inlet or outlet.
- Brass or Stainless Steel fittings.
- Flanges
- SJO Cord
- Elbow on Outlet
- Stainless Steel Tee
- Various volts and Watts
- Custom configurations
- 1/2", 5/8" and 3/4" diameters available
- Optional Thermocouple at outlet for temperature control.

SPECIFICATIONS

- Maximum Amps: 10
- Maximum CFM: 10
- Use clean air only.
- Heat air to temperatures as high as 1000° F.

APPLICATIONS

Marathon Heater manufactures and stocks several variations of 1/2'' diameter air heaters for:

- Heat Staking
- Shrink Fitting
- Plastic Welding
- Laminating
- Sealing
- Drying





STOCK LIST

THE FOLLOWING HEATERS ARE IN STOCK FOR IMMEDIATE DELIVERY								
Stock #	Volts	Watts	Min. Flow Rate (CFM)	Connection	Diameter	Length	Dimensions	
AH50050R	120	400	4	36" Leads	.500			
AH50050T	240	400	4	36" Leads	.500			
AH50050V	120	600	5.5	36" Leads	.500			
AH50050X	240	600	5.5	36" Leads	.500			
AH50050S	120	400	4	3 prong socket	.500			
AH50050U	240	400	4	3 prong socket	.500			
AH50050W	120	600	5.5	3 prong socket	.500			
AH50050Y	240	600	5.5	3 prong socket	.500			

Fittings can be added to any of the above heaters.

- Add the following numbers to the part number when ordering.
- For example: AH50050R-1 for a 120 volt, 400 watt with 1/8 FPT fitting on inlet.

Prefix	Description
-1	1/8" FPT fitting on inlet
-2	3/8" MPT fitting on inlet
-3	1/8" FPT fitting on outlet
-4	3/8" MPT fitting on outlet
-5	1/8" FPT fitting on inlet, 1/8" FPT on outlet
-6	3/8" MPT fitting on inlet, 3/8" MPT on outlet
-7	1/8" FPT fitting on inlet, 3/8 MPT on outlet
-8	3/8" MPT fitting on inlet, 1/8" FPT on outlet.

